



Lamons IsoTek Large Diameter Verification

Please complete for accurate product selection, quote, and drawing.

Date: _____

P.O. Number: _____

Part number, if available: _____

Order Number: _____

Project Name: _____

FLANGE INFORMATION

Flange-face finish between 125-250 RA: Yes ☐ No ☐

Flange type: Raised face ☐ Flat face ☐ Slip-on ☐

Flange nominal size: _____

Flange pressure class: _____

Flange I.D.: _____

Flange O.D.: _____

Cement lining (CL): Yes ☐ No ☐

Provide CL: I.D. _____ O.D. _____

Bolt circle (dia.): _____

Bolt holes (qty.): _____

Bolt hole sizes (dia.): _____

Bolt sizes: _____

B7 hardware suggested.

Flange #1 thickness: _____

Flange #2 thickness: _____

Spacer/blind flange thickness (if used): _____

Flange specification: ANSI ☐ AWWA ☐ API ☐
MSSP-44 ☐ DIN ☐ JIS ☐ DIP ☐

Flange spec for application: Water ☐

AWWA Class & Table: _____
Energy ☐

Series: A ☐ B ☐

GASKET INFORMATION

Brand name: ISOGUARD NSF ☐ ISOGUARD ☐
DEFENDER ☐ DEFENDER FS ☐ ISOKAMM ☐
Matrix ☐

Gasket type: Type E ☐ Type F ☐

Retainer: G10 ☐ G10 (NSF) ☐ G11 ☐ Phenolic ☐
G10S ☐ G11S ☐ 316SS ☐

Seal element: EPDM NSF ☐ EPDM ☐ Nitrile ☐
Teflon ☐ Silicone ☐ Mica ☐

Sleeves: G10 ☐ Mylar ☐ G11 ☐ Nomex ☐ Mica ☐

Isolation/Retainer washers: G10 ☐ G11 ☐ Mica ☐
HC coated ☐

Back-up washers: Steel ZP ☐ 316SS ☐ 304SS ☐
HC coated ☐

Custom sleeve length: _____

Sleeve/washer configuration: Single washer set ☐
Double washer set ☐

Additional notes: _____

Company name (print): _____

Your name: _____

Signature: _____

Date: _____

Effective: 10-11-2022